

HydraX™ Category 5e

U/UTP 24AWG Patch Cords



HydraX™ Category 5e U/UTP unshielded patch cords are manufactured with high quality unshielded 4-pair Cat. 5e stranded cable. Available in both PVC or LSOH jacket.

The snagless design prevents tab breakage and the slim type boot for high-density applications.

Features & Standards

Meets ANSI/TIA-568-C.2 Category 5e

ISO 11801 Class D

Available in 5 colors

RoHS compliant

Applications

100 Base-TX Fast Ethernet and 10 Base-T

155 Mbps ATM and 4/16 Mbps Token Ring.

Voice application and ISDN.

Multimedia application.

SPECIFICATION

Cable Conductor	24AWG stranded bare copper
Cross-Filler	N/A
Shielding	N/A
Cable Diameter	5.30 ± 0.2mm
Cable Outer Jacket	PVC or LSZH
Plug Type	RJ45
Plug Contacts	50 µm Gold plated
Type of Strain Relief	Molding Type
Durability of Plug	750 cycles

HydraX™ Category 5e

U/UTP 24AWG Patch Cords

ORDERING INFORMATION

Product Description	Part Number
C5e U/UTP Patch cord, PVC Jacket Yellow color, 0.5m	PC-C005eC1005-YL
C5e U/UTP Patch cord, LSOH Jacket, Grey color, 0.5m	PC-C005eC2005-GY
C5e U/UTP Patch Cord, PVC Jacket, Red color, 1.5m	PC-C005eC1015-RD
C5e U/UTP Patch Cord, LSOH Jacket, Yellow color, 1.5m	PC-C005eC2015-YL
C5e U/UTP Patch Cord, PVC Jacket, Blue color, 15m	PC-C005eC1150-BL
C5e U/UTP Patch Cord, PVC Jacket, Grey color, 15m	PC-C005eC1150-GY

** PC-CAABCDXXX-YY

1) AA= Constructure (00/U-UTP, 01/U-FTP, 10/F-UTP, 11/F-FTP, 21/S-FTP)

2) B = Category (5e, 6, 6a..)

3) C = Conductor size (C/standard AWG, R/small AWG, S/Solid cable)

4) D = Type of Jacket (0/PE ; 1/PVC ; 2/LSOH)

5) XXX = Length (015/1.5m, 030/3m, 100/10m)

6) YY = Color code (WH/White, RD/Red, YL/Yellow, GY/Grey, BL/Blue)