

HydraX™ Category 6

F/UTP 26AWG Patch Cords



HydraX™ Category 6 F/UTP shielded patch cords are manufactured using high quality shielded 4-pair Cat. 6 stranded cable. Available in both PVC or LSOH jacket.

The snagless design prevents tab breakage and the slim type boot for high-density applications.

Features & Standards

Meets ANSI/TIA-568-C.2 Category 6 and ISO 11801 Class E channel requirements

Backwards compatible to all lower rated category components

RoHS compliant

Applications

10 Base-T, 100 Base-TX Fast Ethernet, 1000 Base-T Gigabit Ethernet (IEEE 802.3)

155/622 Mb/s ATM

Broadband/baseband Analog Video

Voice over internet protocol (VoIP)

SPECIFICATION

Cable Conductor	26AWG stranded bare copper
Cross-Filler	PE
Shielding	Aluminum mylar foil tape
Cable Diameter	6.20 ± 0.2mm
Cable Outer Jacket	PVC or LSZH
Plug Type	RJ45
Plug Contacts	50 µm Gold plated
Type of Strain Relief	Molding Type
Durability of Plug	750 cycles

HydraX™ Category 6

F/UTP 26AWG Patch Cords

ORDERING INFORMATION

Product Description	Part Number
C6 F/UTP 26awg Patch cord, PVC Jacket Red, 0.5m	PC-C106C1005-RD
C6 F/UTP 26awg Patch cord, LSOH Jacket Grey, 1.0m	PC-C106C2010-GY
C6 F/UTP 26awg Patch Cord, PVC Jacket Grey, 3.0m	PC-C106C1030-GY
C6 F/UTP 26awg Patch Cord, LSOH Jacket Red, 5.0m	PC-C106C2050-RD
C6 F/UTP 26awg Patch Cord, LSOH Jacket Yellow, 10m	PC-C106C2100-YL
C6 F/UTP 26awg Patch Cord, PVC Jacket Blue, 15m	PC-C106C1150-BL

** PC-CAABCDXXX-YY

1) AA= Constructure (00/U-UTP, 01/U-FTP, 10/F-UTP, 11/F-FTP, 21/S-FTP)

2) B = Category (5e, 6, 6a..)

3) C = Conductor size (C/standard AWG, R/small AWG, S/Solid cable)

4) D = Type of Jacket (0/PE ; 1/PVC ; 2/LSOH)

5) XXX = Length (015/1.5m, 030/3m, 100/10m)

6) YY = Color code (WH/White, RD/Red, YL/Yellow, GY/Grey, BL/Blue)