

HydraX[™] Voice Patch Cord 110 Type Cat. 5e Patch Cords



HydraX[™] 110 patch cords are used as jumper cords or end-user patch cords. These patch cords come in either 1 Pair, 2 Pairs or 4 Pairs and have 110 to 110 or 110 to RJ45 Plug. The standard lengths are 1, 2, 3 & 4 meters.

The connectors use premium grade Phosphor Bronze contacts suitably plated for long life. These contacts are specially designed to accommodate solid wireas well as stranded conducts from 22 to 26 AWG diameter.

Features & Benefits

Meets ANSI/TIA-568-C.2 Category 5e

Applied with 110 kit conveniently and prolong the service life of 110 kit.

A seamless connection between the 110 kit and RJ45 patch panel.

Suitable for all audio communication systems, multimedia and otherhigh-speed applications

Applications

Ethernet 1000 Base-T, 100 Base-T ; 10 Base-T

Token ring 4/16

155 Mb/s ATM, 1.2Gb/s ATM

Broadband/baaseband Analog Video

Video Protocal - IPTV, digital video

SPECIFICATION

Cable Conductor	AWG 24 * 7 stranded cable
Cross-filler	N/A
Shielding	N/A
Number of Pairs	1/2/4
Cable Diameter	3.0mm/4.0mm/5.1mm
Cable Outer Jacket	PVC or LSZH
Plug Type	RJ45 or 110
Durability of Plug	200 times





HydraX[™] Voice Patch Cord

110 Type Cat. 5e Patch Cords

ORDERING INFORMATION

Product Description	Part Number
1-pair 110-RJ45 voice patch cord, PVC jacket 1mtr	VPC-301010
2-pair 110-110 voice patch cord, LSOH jacket 5mtr	VPC-442010
4-pair 110-RJ45 voice patch cord, LSOH jacket 1mtr	VPC-502010

** VPC-ABCDDD

1) A = Plug A (0/RJ45, 1/RJ11, 2/RJ12, 3/1pair 110, 4/2pairs 110, 5/4pairs 110, 6/5pairs 110)

2) B = Plug B (0/RJ45, 1/RJ11, 2/RJ12, 3/1pair 110, 4/2pairs 110, 5/4pairs 110, 6/5pairs 110)

3) C = Type of jacket (0/PE, 1/PVC, 2/LSOH)

4) DDD = Length (015/1.5m, 030/3m)